



TARGET

Having elastic and soft touch of transfoil printing.

PROPERTY

It is water based.

During the use, does not dry and block the screen.

The washing fastness is high.

Suitable to ecological standarts.

SAFETY

It is ecological, does not contain harmful chemicals.

Should be avoided from eye contact and ingestion.

Please kindly see product safety data sheet for detailed information.

STORAGE

Keep containers dry and tightly closed. Store in ventilated place between (5 - 35) °C - (41 - 95) °F of temperature.

Recommended shelf life is 12 months after the production.

PACKING

30 Kg

APPLICATION

Fabric : All type of fabric.

Printing : Single layer printing is recommended. Foil paper is pressed after curing.

Mesh : (32 - 43) cm - (80 - 100) Inch

Squeegee : 55 - 65 Shore and U type.

Curing : (150 - 160) °C - (302 - 320) °F
1,5 - 2 minutes.

Hand Press : (150 - 170) °C - (302 - 338) °F
(4 - 6 bar) - (10 - 15 second)

Band Press : (150 - 170) °C - (302 - 338) °F
(4 - 6 bar) - (20 - 25 second)

Mixture : To reduce the viscosity % 1-3 W 401 can be added but do not use the water. Stir well before use.

Clean up : The screen should be cleaned with water.