

TECHNICAL DATA SHEET W 460 FLOCK PASTE



TARGET

Having elastic and soft touch of flock printing.

PROPERTY

It is water based. During the use, does not dry and block the screen. The washing fastness is high. Suitable to ecological standarts.

SAFETY

It is ecological, does not contain harmful chemicals. Should be avoided from eye contact and ingestion. Please kindly see product safety data sheet for detailed information.

STORAGE

Keep containers dry and tightly closed. Store in ventilated place between (5 - 35) °C - (41 - 95) °F of temperature.

Recommended shelf life is 8 months after the production.

PACKING

30 Kg

The information on this form is based on our best experience and knowledge. It would not be counted as warranty or quality specification. If requested, our technical staff is at your service.

APPLICATION

Fabric : All type of fabric.

Printing : Flock paste is first printed on the fabric, then flock dust spread to the surface with a flocking machine followed by curing.

(70 100) lash

wesn	: (27 - 43) cm - (70 - 100) Inch
Squeegee	: 55 - 65 Shore and U type.
Curing	: (150 - 160) °C - (302 - 320) °F 1,5 - 2 minutes and double cured.

Mixture : To be added % 2-3 W 400. After adding W 400, the average shelf life is 8 hours. To reduce the viscosity % 1-3 W 401 can be

added but do not use the water. Stir well before use.

Clean up : The screen should be cleaned with water.